

**Products Specification**

**Shenzhen Rmede Technology Co., Ltd**

Email: sales@Rmede.com

Http://www.Rmede.com

<b>SPECIFICATION</b>		PREPARE	CHECK	APPROVE
MODEL:	USED IN:			
ISSUE DATE :				
COMMON/UNITE	DOC. NO:		REV.: 1.0	PAGE: 1 OF 1

**3PN0512S SMART NIMH BATTERY CHARGER**

NO	ITEM	UNIT	SPECIFICATION	REMARK
<b>INPUT</b>				
01	RATING INPUT	V ac	100~240Vac 50/60Hz	
02	INPUT RANGE	V ac	90~264Vac	
03	RATING INPUT CURRENT	A	0.1Arms	INPUT:230V OUTPUT:Full load
04	MAX. INPUT POWER	W	8	
<b>OUTPUT</b>				
05	RATING OUTPUT VOLTAGE	V dc	9V	
06	OUTPUT VOLTAGE RANGE	V dc	6VDC ~ 12VDC	12V is open circuit voltage
07	SUIT WITH BATTERY	Ah	4.8~7.2V 0.6~3Ah NIMN/NICD	
08	CHARGE CURRENT	A	0.45 A (+0.05A)	
09	TRICKLE CURRENT	A	<0.05	
11	INNER TIMMER(default)	hour	8	Defined by user
12	MAX. OUTPUT POWER	W	5W	
13	HOLD-ON TIME	ms	NC	Input: 230Vac Output: Full load
14	RIPPLE CURRENT	mA	20	Input: 230Vac Output: Full load
15	MAIN CHARGE END CONDITION		-ΔV > 5mV /CELL(TYP)	
16	LED INDICATION		RED: MAX CHARGE GREEN: FINISHED	
17	Output Short-circuit Protection	-	YES	
18	Output Reverse Protection EFFICIENCY	%	95%	At max. load
<b>ENVIRONMENT</b>				
19	OPERATE TEMP.	°C	-10 ~ +40	Full load & natural convection.
20	OPERATE HUMIDITY	%RH	< +90	Relative humidity, non-condensing.
21	STORAGE TEMP.	°C	-40 ~ +70	
22	STORAGE HUMIDITY	%RH	0 ~ +95	Relative humidity, non-condensing.
23	COOLING	-	Natural convection	
24	TEMP. FACT	%	--	
25	VIBRATION		5MM/50HZ/600S	Non-operating condition.
26	IMPACT		1 meter drop test >= 3 times	Non-operating condition.
<b>MECHANICAL</b>				
27	WEIGHT	g	100	
28	SIZE	mm	65X61X26	Casing only
29	DC Cable & CONNECTER	-	Defined by user	
<b>SAFETY</b>				
30	TEMP. RISE	°C	< 40 on casing	At any line and Max. Load
31	SAFETY STANDARD	-	EN60335 or EN60950	
32	EMC	-	EN55013 or EN55022B	
33	MTBF	hrs	30000	
34	ESD	kV	8.0	
35	HI-POT	V	i/p to o/p: 3000 (1 min.)	For final unit, cut-off current =10mA